

JAYEM MULTI-PURPOSE TOWER HOIST



SPECIAL FEATURES

- Jayem Tower hoist is designed for vertical transport solution on construction sites for carrying concrete, TMT bars, bricks, tiles etc.
- Jayem Tower Hoist are offered with two different capacities i.e. 1000 Kgs gross and 1200kgs gross capacities.
- Safety features include fail safe break motor, limit switch for top and boom.
- Anfalling safety hooks to cater wire rope failure and fully covered electrical motor and gearbox.
- Electrical control panel with remote for operation of hoist all the material used are of schneider, phase preventer, over load relays & MCB's for safe and easy working of Hoist.

OPTIONAL

- Rebar Carrier 6250mm Length (Customised)
- Brick/Tiles Bucket L-1200mm x W-675mm x H-600mm (Customised)

TECHNICAL SPECIFICATIONS:-

MODEL	JTH-1000	JTH-1200
Maximum Load	1000kgs	1200kgs
Net Load	750kgs	1000kgs
Wire Rope	12mm Usha martin	12mm Usha martin
Speed	0.33m/sec	0.33m/sec
Height Maximum	120 Mtr	120 Mtr
Geared Motor	7.5 Kw(10.0 H.P) Break Motor	9.3 Kw(12.5 H.P) Break Motor
Wall tie interval	6m	6m
Mast Section	500 x 400 x 1500	500 x 400 x 1500
	Angle 50x50x6	Angle 50x50x6
Concrete bucket	300L	400L

Note: Due to continuous improvement in designs, the above specifications are subject to change without prior notice.



JAYEM MANUFACTURING COMPANY PVT. LTD.
Assisting Global Infrastructure

AN ISO 9001:2000 COMPANY

Head Office :
C-99, Sector-4, Noida-201301 (U.P.)
Mob. : +91-9810764683, 981038890
Website : www.jayempl.com

Works :
B2/10, Site-B, Surajpur Industrial Area,
Greater Noida (UP) India
Mob. : +91-9654959011, 9810388900
Email : jaymepl.acd@gmail.com



JAYEM

JAYEM' TOWER HOIST



DESCRIPTION:

JAYEM' Make Tower Hoist is used to lift the building material like cement, Concrete, sand, bricks, aggregate etc. upto the height of 60 meter. The tower hoist is powered either by diesel engine or electric motor.

Technical Specifications:

MODEL	JTH-500	JTH-600
Power	10.0 H.P	15.0 H.P
Gross Capacity	500 Kgs	600 Kgs
Maximum Height	60 meter or 200 feet	60 meter or 200 feet
Maximum Speed	25-30 m/min	25-30 m/min
Mast Section Main Angle	50mm x 50mm x 5mm	50mm x 50mm x 5mm
Concrete /Brick Bucket	150 Liter	200 Liter
Wheels	Pneumatic	Pneumatic

Note: Due to connues improvement in designs, the above specifacons are subject to change without prior noce.



JAYEM MANUFACTURING COMPANY PVT. LTD.

Assisting Global Infrastructure

AN ISO 9001:2000 COMPANY

Head Office :
C-99, Sector-4, Noida-201301 (U.P.)
Mob. : +91-9810764683, 981038890
Website : www.jayempl.com

Works :
B2/10, Site-B, Surajpur Industrial Area,
Greater Noida (UP) India
Mob. : +91-9654959011, 9810388900
Email : jaymepl.acd@gmail.com